










Comfort Mini










 LxhxP	Dimensions (mm)	700 x 550 x 453
 kg	Net weight kg	122
 Ø	Smoke outlet diameter (Ø mm)	80
 m ³	Heatable m ³	195 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,5 - 6,8
%	Efficiency %	92,9 - 86,4
	Hourly consumption (kg/h)	0,7 - 1,6
	Feed box Total capacity (kg)	~ 12
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	80 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort Mini Crystal










 LxhxP	Dimensions (mm)	700 x 550 x 489
 kg	Net weight kg	115
 Ø	Smoke outlet diameter (Ø mm)	80
 m³	Heatable m ³	195 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,5 - 6,8
%	Efficiency %	92,9 - 86,4
	Hourly consumption (kg/h)	0,7 - 1,6
	Feed box Total capacity (kg)	~ 12
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	80 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort P70H49










 LxhxP	Dimensions (mm)	695 x 488 x 514
 kg	Net weight kg	131
 Ø	Smoke outlet diameter (Ø mm)	80
 m³	Heatable m ³	205 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	2,9 - 7,1
%	Efficiency %	91,7 - 90
	Hourly consumption (kg/h)	0,7 - 1,7
	Feed box Total capacity (kg)	~ 10
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	80 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενεργεια IE IA **A+**

Comfort Maxi










 LxhxP	Dimensions (mm)	640 x 616 x 716
 kg	Net weight kg	132
 Ø	Smoke outlet diameter (Ø mm)	80
 m³	Heatable m ³	255 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,4 - 8,9
%	Efficiency %	90,7 - 88,7
	Hourly consumption (kg/h)	0,8 - 2
	Feed box Total capacity (kg)	~ 28
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	80 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort P70










 LxhxP	Dimensions (mm)	695 x 547 x 617
 kg	Net weight kg	140
 Ø	Smoke outlet diameter (Ø mm)	80
 m ³	Heatable m ³	278 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	2,9 - 9,7
%	Efficiency %	91,7 - 86,6
	Hourly consumption (kg/h)	0,7 - 2,4
	Feed box Total capacity (kg)	~ 20
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	80 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort P70 Air










 LxhxP	Dimensions (mm)	670 x 530 x 561
 kg	Net weight kg	125
 Ø	Smoke outlet diameter (Ø mm)	80
 m ³	Heatable m ³	287 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3 - 10
%	Efficiency %	90,4 - 90,9
	Hourly consumption (kg/h)	0,7 - 2,2
	Feed box Total capacity (kg)	~ 15
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	23 - 75

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort P85










 LxhxP	Dimensions (mm)	814 x 550 x 636
 kg	Net weight kg	145
 Ø	Smoke outlet diameter (Ø mm)	80
 m ³	Heatable m ³	344 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,5 - 12
%	Efficiency %	91,3 - 91,8
	Hourly consumption (kg/h)	0,8 - 2,6
	Feed box Total capacity (kg)	~ 16
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	25 - 100

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort Plus










 LxhxP	Dimensions (mm)	702 x 576 x 636
 kg	Net weight kg	161
 Ø	Smoke outlet diameter (Ø mm)	80
 m³	Heatable m ³	315 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,2 - 11
%	Efficiency %	96,1 - 90,8
	Hourly consumption (kg/h)	0,7 - 2,5
	Feed box Total capacity (kg)	~ 16
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	100 - 130

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort Plus Crystal










 LxhxP	Dimensions (mm)	702 x 576 x 673
 kg	Net weight kg	170
 Ø	Smoke outlet diameter (Ø mm)	80
 m ³	Heatable m ³	315 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,2 - 11
%	Efficiency %	96,1 - 90,8
	Hourly consumption (kg/h)	0,7 - 2,5
	Feed box Total capacity (kg)	~ 16
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	100 - 130

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**

Comfort P85 Plus

 LxhxP	Dimensions (mm)	814 x 550 x 636
 kg	Net weight kg	160
 Ø	Smoke outlet diameter (Ø mm)	80
 m³	Heatable m ³	344 (Referred to the need of 30 kcal/h x m ³)
kW-N	Nominal thermal power (kW)	3,5 - 12
%	Efficiency %	92 - 91,1
	Hourly consumption (kg/h)	0,8 - 2,6
	Feed box Total capacity (kg)	~ 16
	Convection fan	Yes
	Remote Control	Yes
	Foreseen for external thermostat (TA)	Yes
w	Electric consumption (W)	75 - 150

CERTIFICATIONS

EN
15a B-VG
FlammeVerte
BlmSchV II

ENERG Y IJA
енергия · ενέργεια IE IA **A+**